

Specification

SLIMDUCT MD

2020 January 31st

Inaba Denki Sangyo. Co., Ltd.
Research & Development division

1. Application

This specification applies to SLIMDUCT MD

2. Product Specification

Specification of SLIMDUCT MD is as per Table 1.

Table 1

Product Name	Product No.	Size		Material	Color Tone	Temperature
Slim Duct MD	MD	75	85	PVC	Neo White (Munsell N9.0)	-4° F~ 140° F (Product Surface)
Wall Inlet	MW	75	85			
Wall Inlet for air conditioner cap	MWM	75S 75L	85			
Adjustable Wall Inlet	MWS	75L	85			
90° Flat Elbow	MK	75	85			
45° Flat Elbow	MKF	75	85			
90° Twist Elbow	MN	75	85			
90° Inside Vertical Elbow	MCI	75	85			
90° Outside Vertical Elbow	MCO	75	85			
90° Outside mini Vertical Elbow	MCOM	75	85			
90° Adjustable Vertical Elbow	MCS	75	85	ABS		
Coupler	MJ	75	85	PVC		
Tee	MT	75	85			
Flexible Bend Coupler	MFJ	-----	85			
Flexible Bend	MF	75	85	PE+EVA		
Soffit Inlet	MP	75	85	PVC		
Gasket (End Fitting)	MS	75	85	Body: PVC Edge: Rubber		

※ SLIMDUCT MD series is for Indoor use only.

※ SLIMDUCT MD series is made with flame retardant materials.(Exclude ABS parts)