



## Insulated lineset for ductless AC

Paircoil copper tube linesets are designed for efficiency, coming pre-paired and pre-insulated to significantly speed up installation time. Built to meet the highest industry standards, it boasts nine ASTM ratings, including the ASTM E84 (25/50). Made from high-quality annealed copper, Paircoil is easy to flare and flexible enough to bend effortlessly. The insulation is both robust and pliable, offering superior protection against wear and tear over the long term. A2L compatible and available in a range of sizes, Paircoil is the go-to choice for contractors who demand reliability and efficiency.

Contact us today:

[www.InabaDenko-America.com](http://www.InabaDenko-America.com)



## TECH INFO



Length markers at every foot for fast, accurate measuring and cutting.



Easily separated by hand

### ASTM Ratings

INSULATION	
ASTM E84 (25/50)	Surface Burning Characteristics
ASTM C1763	Water Absorption
ASTM E96	Water Vapor Permeability
ASTM C411 & C447	Maximum Use Temperature
ASTM C1427	Linear Shrinkage
ASTM G154	UV Exposure
ASTM C518	Thermal Conductivity

COPPER TUBE	
ASTM B280 C12200 DHP	Phosphorus Deoxidized Copper Seamless Tube
ASTM B1003	Pressure



[Click here for full product description](#)

## FEATURES

- Labor-saving single-run installation of both lines.
- Embossed film coating allows easier installation.
- Fire retardant cross-linked polyethylene insulation.
- Easily shapes to fit any application.
- R410A compatible.
- A2L refrigerant compatible.

Item No.	Liquid line OD (Inch)	Suction line OD (Inch)	Insulation thickness (Inch)	Length (Feet)	Type
PC-2325-NA	1/4	3/8	1/2	25	Paired
PC-2335-NA	1/4	3/8	1/2	35	Paired
PC-2350-NA	1/4	3/8	1/2	50	Paired
PC-2382-NA	1/4	3/8	1/2	82	Paired
PC-2425-NA	1/4	1/2	1/2	25	Paired
PC-2435-NA	1/4	1/2	1/2	35	Paired
PC-2450-NA	1/4	1/2	1/2	50	Paired
PC-2482-NA	1/4	1/2	1/2	82	Paired
PC-2525-NA	1/4	5/8	1/2	25	Paired
PC-2535-NA	1/4	5/8	1/2	35	Paired
PC-2550-NA	1/4	5/8	1/2	50	Paired
PC-2582-NA	1/4	5/8	1/2	82	Paired
PC-3525-NA	3/8	5/8	1/2	25	Paired
PC-3535-NA	3/8	5/8	1/2	35	Paired
PC-3550-NA	3/8	5/8	1/2	50	Paired
PC-3582-NA	3/8	5/8	1/2	82	Paired
PC-3625-NA	3/8	3/4	1/2	25	Paired
PC-3635-NA	3/8	3/4	1/2	35	Paired
PC-3650-NA	3/8	3/4	1/2	50	Paired
PC-3682-NA	3/8	3/4	1/2	82	Paired