



SLIMDUCT™ RD

The **Slimduct RD Commercial Lineset Cover** offers a sleek, cost-effective solution for protecting and concealing multiple linesets in VRF/VRV systems. Designed for flexibility,

it installs easily and adapts to any layout or orientation. A smart alternative to custom ducting, Slimduct RD saves labor while delivering a clean, professional finish.



[Click here for full product description](#)



[Check out our Youtube Playlist](#)

KEY FEATURES

Attractive

Slimduct RD encloses the multiple lines used by variable refrigerant flow/volume (VRF/VRV) multi-split systems. Requiring less space than traditional racking/jacketing system, its compact design delivers a clean, professional and finished look to any rooftop project. It blends in perfectly with any type of commercial building.

Multiple Applications

A wide array of fittings, including risers, vertical mountings, and under-slab mountings, are readily available to easily customize while on the job site, during the installation process. Slimduct RD can also be installed in any orientation.

Easy to Assemble

Slimduct RD is engineered to make installation a time-saving process. No special tools are required to assemble and connect the interlocking covers together. The screws needed, are included with the product.

Durability

Fabricated from sheets of high-grade, corrosion-resistant and hot-dipped, galvanized steel, Slimduct RD is coated with zinc, aluminum, and magnesium. This scratch, abrasion and corrosive resistant coating offers better protection than stainless steel, even in highly corrosive environments such as coastal areas.



TECHNICAL SPECS

Material

Highly corrosion-resistant hot-dip galvanized steel sheet has a coating layer of zinc, 6% aluminum, and 3% magnesium.

Tensile Strength

More than 274.6N/mm² (=28kgf/mm²) (=39.885psi)

Salt Tolerance

Salt Resistant

Stretch

More than 28%