

Specifications

Lineset Cover System SLIMDUCT PD

May 19, 2020

Inaba Denki Sangyo. Co., Ltd.

Research & development division

1. Application :

- This Specifications shall be applied to SLIMDUCT PD Series.

2. Product Specifications :

Product Specifications of SLIMDUCT PD Series are shown in the Table-1;

Table-1 Product Specifications

Product Name	Item No.	Applicable Size	Material	Insertion Length of Straight Duct (mm)(inch)	
				PD-90/120	PD-140
SLIMDUCT PD	PD	90,120,140	PVC		
MOUNTING COUPLER	PDB-N	90,120,140	PVC	49(≠1-15/16")	52(≠2-3/64")
MOUNTING COUPLER	PDBK	90,120	PVC	48(≠1-59/64")	—
90°ELL	PDE	90,120,140	PVC	32(≠1-1/4")	40(≠1-9/16")
45°ELL	PDF	90,120,140	PVC	32(≠1-1/4")	40(≠1-9/16")
ADJUSTABLE ELL	PDKS	90,120	PVC	32(≠1-1/4")	—
STANDARD COUPLER	PDJ	90,120,140	PVC	32(≠1-1/4")	40(≠1-9/16")
END FITTING	PDC	90,120,140	PVC	32(≠1-1/4")	40(≠1-9/16")
TEE	PDT	90,120,140	PVC	32(≠1-1/4")	40(≠1-9/16")
REDUCER	PDI	120-90,140-120	PVC	32(≠1-1/4")	32(≠1-1/4")
WALL FLANGE	PWP-N	90,120,140	Body : PVC Decorative Packing: Elastomer		
WALL FLANGE	PSP	90,120	PVC		
WATER STOP WALL FLANGE	PDP	90,120	PVC		
T-BRANCH	PDJTN	90 · 120 · 140 All size covered by 1SKU	AES	30(≠1-11/64") or more	30(≠1-11/64") or more
PD-SD COUPLER	PSDR	90,120	PVC	32(≠1-1/4")	—
FITTING MOUNT CLIP	PDL	90 · 120 · 140 All size covered by 1SKU	SUS 304		
FITTING MOUNT CLIP FOR BACK OF CONNECTION ACCESSORIES	PDH	90 · 120 · 140 All size covered by 1SKU	SUS 304		
REINFORCEMENT ACCESSORY FOR NOTCH	PDK	90 · 120 · 140 All size covered by 1SKU	PVC		
SUPPORTER BAND	PDY	90,120,140	SUS 304		
PD DUCT FIXING SADDLE	PDU	90,120,140	SUS 304		

Usage Temperature Range : -20~60°C (-4°F-140°F)(temperature on the surface of product)

Color Tone : Ivory (Munsell 5Y8/1, Japan Paint Manufacturers Association D25-80B)

※SLIMDUCT PD Series is made from flame retardant material.