

# Specifications

## Horizontal Pipe Support SUPERLOCK V TYPE SRV

January 31, 2020

Inaba Denki Sangyo. Co., Ltd.  
Research & development division

## 1. Application

This specification applies to SUPERLOCK V TYPE SRV.

## 2. Product Specifications

Table 1 shows the specifications and allowable static load of SRV, and Table 2 shows the dimensions.

Table-1 Specifications and Allowable Static Load

Item No.	Material and Surface treatment	Allowable static load
SRV- 24B	[Main body] Material: Hot rolled steel plate Surface treatment: Electro-galvanized (Unicrome plating)  [Springs] Material: Stainless steel	196N (20kgf) (≈44 lbs)
SRV- 35B		
SRV- 46B		
SRV- 58B		
SRV- 69B		
SRV-710B		
SRV-811B		
SRV-912B		
SRV-1012B		
SRV-1114B		

Table 2 Dimensions

Model No.	Dimension (mm)						Body thickness	Clip thickness
	L1	L2	H	A	B			
SRV- 24B	70 (≐2-7/8")	57.5 (≐2-3/8")	95 (≐3-3/4")	59 (≐2-3/8")	37 (≐1-1/2")	1.0 (≐0.04")	1.0 (≐0.04")	
SRV- 35B	70 (≐2-7/8")	57.5 (≐2-3/8")	101 (≐4")	67 (≐2-3/4")	37 (≐1-1/2")			
SRV- 46B	74 (≐3")	61.5 (≐2-1/2")	112 (≐4-1/2")	76 (≐3")	41 (≐1-5/8")			
SRV- 58B	84 (≐3-3/8")	71.5 (≐2-7/8")	121 (≐4-7/8")	85 (≐3-3/8")	51 (≐2-1/8")			
SRV- 69B	84 (≐3-3/8")	71.5 (≐2-7/8")	128.5 (≐5-1/8")	92 (≐3-5/8")	51 (≐2-1/8")			
SRV-710B	94 (≐3-3/4")	81.5 (≐3-1/4")	129 (≐5-1/8")	94 (≐3-3/4")	61 (≐2-1/2")			
SRV-811B	94 (≐3-3/4")	81.5 (≐3-1/4")	138 (≐5-1/2")	102 (≐4-1/8")	61 (≐2-1/2")			
SRV-912B	94 (≐3-3/4")	81.5 (≐3-1/4")	144 (≐5-3/4")	108 (≐4-3/8")	61 (≐2-1/2")			
SRV-1012B	103 (≐4-1/8")	90.5 (≐3-5/8")	155 (≐6-1/8")	119 (≐4-3/4")	70 (≐2-7/8")			
SRV-1114B	113 (≐4-1/2")	100.5 (≐4")	159 (≐6-3/8")	123 (≐4-7/8")	80 (≐3-1/4")			

